



L'huile des records du monde

## YACOPRO SAE 5W-40

**Synthetic oil for high performing gasoline and turbo Diesel engines**

### APPLICATIONS

For gasoline and Diesel engines, including Diesel direct injection, VW Group injector pump and Diesel FAP (particle filter) engines.

Recommended in passenger cars and light commercial vehicles used under severe driving conditions (highways, urban traffic...) for maximum 15000 km/1 year oil drain interval.

### MAIN PHYSICAL DATA

		Units	5W-40
Density at	20° C	kg/m <sup>3</sup>	852
Kinematic viscosity at	40° C	mm <sup>2</sup> /s	83
Kinematic viscosity at	100° C	mm <sup>2</sup> /s	13.7
Viscosity index			169
Flash point Cleveland open cup		° C	>220
Pour point		° C	- 36
Dynamic viscosity at	- 30° C	mPa.s	<6600

The data given in this table are typical production values and cannot be considered as specifications.

### PROPERTIES & ADVANTAGES

- “Low SAPS” formulation for excellent protection of particle filters
- Very good detergent and dispersant properties
- Good engine protection against wear and corrosion
- SAE 5W40 grade provides very quick oil flow at start-ups and reduces wear even under very cold temperature

### SPECIFICATIONS

**ACEA C3; ACEA A3/B4-07; API SM/CF**

**BMW LL-04; FORD WSS-M2C917-A; Mercedes MB 229.31**

**Renault RN0710/0700; VW 502.00/505.00/505.01**

