



L'huile des records du monde

## MVX Race 4T - SAE 15W-50

100 % synthetic oil for 4 stroke competition motorbikes

### USES

Especially formulated and developed on competition motorbikes.

Well adapted and recommended for : speed, enduro, cross,....

Perfect lubrication of gear boxes and oil batch clutches.

Can be mixed to similar lubricants.

### MAIN CHARACTERISTICS

		Units	15W-50
Density	20° C	kg/m <sup>3</sup>	854
Kinematic viscosity	40° C	mm <sup>2</sup> /s	124
Kinematic viscosity	100° C	mm <sup>2</sup> /s	18
Viscosity Index			162
Pour Point		° C	-45
Flash Point Cleveland open cup		° C	> 210
Dynamic viscosity at	- 20°C	mPa.s	4500

*The data given in this table are typical production values and cannot be considered as specifications.*

### PROPERTIES & ADVANTAGES

- Good stability of the oil at **high temperature in the more severe conditions**
- Quick and optimal lubrication when starting the engine
- Good level of detergency and dispersivity for the **cleanliness of the engine**
- Excellent protection of the engine against **wear**
- Keeps on the optimal performances of the engine.

### PERFORMANCES

Exclusively developed in competition, **MVX RACE 4T** exceeds widely the performances required by the main OEM.

