



L'huile des records du monde

FORK FLUID 15W

FORK FLUID

APPLICATIONS

Fork oil 15W provides a stiffer damping than the original fluid.

Suitable for conventional forks with frequent duo riding, or high mileage suspensions by helping to compensate over damping of tired springs.

This fluid is part of our YACCO FORK FLUID products range.

For softer damping, use FORK FLUID 2.5W; 5W; 7.5W or 10W according to personal preference; for stiffer damping, use FORK FLUID 20W.

MAIN CHARACTERISTICS

		Units	FORK FLUID 15W
Density at	20° C	kg/m ³	872
Kinematic viscosity at	40° C	mm ² /s	46
Kinematic viscosity at	100° C	mm ² /s	8.3
Viscosity index			157
Pour point		° C	-39
Flash point Cleveland open cup		° C	> 200

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- High-shear stable multi-grade fluid provides progressive operation of the suspension.
- High-viscosity fluid for applications requiring a stiff damping or hot temperature service conditions
- Very good damping feeling under all operation conditions.
- Excellent anti-foam, anti-wear, anti-corrosive and anti-friction properties
- Protects o-rings. Compatible with fork oil seals

