



L'huile des records du monde

MVX 500 2T

100% semi-synthetic oil for 2-stroke motorbike engines

APPLICATIONS

MVX 500 2T is specific and recommended for lubricating 2-stroke engines, with very high working speed and under severe conditions.

Suitable for separated or mixed lubrications.

Mixture: from 2 to 4 %, depending on the OEM's requirements.

MAIN CHARACTERISTICS

	Units	Typical values
Density at 20° C	Kg/m ³	869
Kinematic viscosity at 40° C	mm ² /s	76
Kinematic viscosity at 100° C	mm ² /s	10.9
Viscosity index		131
Pour point	° C	-36
Flash point Cleveland open cup	° C	114
Colour		Blue

The data given in this table are typical values from production and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- Avoid deposits on the exhaust pipe
- High internal engine protection against **rust**
- Very good efficiency against **engine seizing risks**
- Blue colour, allowing its detection in the oil-fuel mixture
- Prevents **sparkplug problems** and piston ring gumming

PERFORMANCES

API TC
ISO-L-EGD

HOMOLOGATIONS

JASO FD

033YCO135

FD

PRODUCT MEETING JASO M345
COMPANY GUARANTEEING THIS PERFORMANCE
YACCO S.A.S.

