



INBOARD 500 4T SAE 10W-40

Semi-synthetic oil for both gasoline & Diesel 4-stroke Inboard and Sterndrive engines

APPLICATIONS -

Semi-synthetic oil for both **Diesel & gasoline 4-stroke Intboard and Sterndrive engines** Suitable for both pleasure and professional fishing boats.

Good protection against corrosion. Keeps engines clean.

MAIN CHARACTERISTICS

		Units	Values
Density at	20° C	kg/m ³	865
Kinematic viscosity at	40° C	mm ² /s	105
Kinematic viscosity at	100° C	mm ² /s	15.5
Viscosity index			156
Dynamic viscosity at	-25°C	mPa.s	6000
T.B.N. (Total Base Number)		mg KOH/g	9.8
Flash Point Cleveland open cup)	°C	225

The data given in this table are typical production values and cannot be considered as specifications

PROPERTIES & ADVANTAGES

- · Semi-synthetic formula for increased thermal stability and reliable long drain intervals.
- This ACEA E9 & ACEA E7 lubricant is suitable for both recent and older engines, including those equipped with depollution systems.
- Meets the latest Tier 4 engines depollution standard, requiring a significant reduction of nitrogen oxides emissions (NOx)
- Low SAPS formula (low levels of sulfated ash, phosphorus and sulfur) for increased protection of post-treatment systems and particulates filters.
- \cdot High detergent-dispersant properties keep engines clean.

SPECIFICATIONS

ACEA E9 & ACEA E7 Caterpillar ECF-3/ECF-2/ECF-1a Deutz DQC III-10 LA MTU Type 2.1 API CJ-4/SM Cummins 20081; Detroit Diesel 93K218 MB 228.31; Man M 3575 Volvo VDS-4



005-LAB/FT/EE16-2015/3377

contact@yacco.com

Before using this lubricant, please check the technical requirements of the manufacturer in the service manual of the equipment