



YACCO
NAUTISME

OUTBOARD 500 4T SAE 10W-30

Semi-synthetic oil for gasoline 4-stroke Outboard engines

APPLICATIONS

Semi-synthetic oil for gasoline 4-stroke Outboard engines used in severe or normal service conditions.

Suitable for use with HONDA, MARINER, MERCURY, SELVA, SUZUKI, TOHATSU, YAMAHA...

MAIN CHARACTERISTICS

		Units	Values
Density at	20° C	kg/m ³	871
Kinematic viscosity at	40° C	mm ² /s	78
Kinematic viscosity at	100° C	mm ² /s	12.1
Viscosity index			151
Dynamic viscosity at	-25° C	mPa.s	5300
Flash Point Cleveland open cup		° C	210

The data given in this table are typical production values and cannot be considered as specifications

PROPERTIES & ADVANTAGES

- Unrivalled engine protection against rust and corrosion in corrosive marine atmosphere (N.M.M.A FC-W approval n° FB-00210R).
- Specific formulation for increased engine protection against buildup formation
- High level of performance meeting powerful engines requirement
- Excellent oxidation resistance and outstanding thermal stability for improved lubrication stability in service.
- Semi-synthetic formulation for increased performances
- 10W viscosity providing fast lubrication at start-up at any ambient temperature

HOMOLOGATIONS

N.M.M.A FC-W

Registration Number: FB-00210R

SPECIFICATIONS

API SL

