



YACCO
NAUTISME

OUTBOARD 500 4T SAE 25W-40

Semi-synthetic oil for gasoline 4-stroke Outboard, Inboard and Sterndrive engines

APPLICATIONS

Semi-synthetic oil for gasoline 4-stroke Outboard, Inboard and Sterndrive engines used in severe or normal service conditions.

Suitable for use with MERCURISER, MERCURY, OMC, VOLVO PENTA,...

MAIN CHARACTERISTICS

		Units	Values
Density at	20° C	kg/m ³	888
Kinematic viscosity at	40° C	mm ² /s	127
Kinematic viscosity at	100° C	mm ² /s	13.8
Viscosity index			105
Dynamic viscosity at	-10°C	mPa.s	5300
Flash Point Cleveland open cup		° C	225

The data given in this table are typical production values and cannot be considered as specifications

PROPERTIES & ADVANTAGES

- Unrivalled engine protection against rust and corrosion in corrosive marine atmosphere (N.M.M.A FC-W approval n° FB-00211R).
- Specific formulation for increased engine protection against deposits formation
- High level of performance meeting powerful engines requirement
- Excellent oxidation resistance and outstanding thermal stability for improved lubrication stability in service.
- Semi-synthetic formulation for increased performances
- 25W40 viscosity providing optimal lubrication in heavily loaded engines used in severe service conditions

HOMOLOGATIONS

N.M.M.A FC-W

Registration Number: FB-00211R

SPECIFICATIONS

API SL

