



L'huile des records du monde

# BVX 500 X– SAE 75W-80

## Synthetic high performance transmission oil

### APPLICATIONS

Multi-purpose transmission oil suitable for all manual transmissions of light vehicles and certain type of commercial vans.

BVX 500 X 75W80 covers a wide range of applications and specifications. It is suitable for use in manual transmissions of a large number of car brands.

### MAIN CHARACTERISTICS

		Units	SAE 75W-80
Density at	20° C	kg/m <sup>3</sup>	852
Kinematic viscosity at	40° C	mm <sup>2</sup> /s	56
Kinematic viscosity at	100° C	mm <sup>2</sup> /s	9.7
Viscosity index			163
Pour point		° C	-45
Flash point Cleveland open cup		° C	>200

The data given in this table are typical production values and cannot be considered as specifications.

### PROPERTIES & ADVANTAGES

- Synthetic-based formula provides increased components protection
- Extreme-pressure and anti-wear properties ensure optimal gear protection under the most severe service conditions.
- Very good compatibility with elastomers.
- Excellent synchromesh operation over full gear's lifetime
- Outstanding anti-foam and filterability properties provide efficient lubrication in all circumstances
- Increased anti-rust and anti-corrosion protection
- Suitable for transmissions of many European and Asian vehicles

### PERFORMANCES

API GL-4

BMW MTF LT-2/ MTF LT-3 • GM 1940182 / 1940764 / 1940768

Honda MTF LT-2/MTF LT-3 • MB 235.10 • MTF 94 • PSA B71 2330

Renault Tranself NFJ / TRJ/TRT/TRZ • Volvo 97308 / 97309

VW G 009 317

