



L'huile des records du monde

# AGRIPRO HJD

## Transmission and hydraulic systems lubricant

### USES

Lubrication of transmissions, hydraulic and gear systems and « immersed brakes » for **agricultural and public works machinery**.

According to the manufacturers recommendations, use either this product or AGRIPRO HF6.

### MAIN CHARACTERISTICS

		Units	Typical values
Density at	20° C	kg/m <sup>3</sup>	887
Kinematic viscosity at	40° C	mm <sup>2</sup> /s	58
Kinematic viscosity at	100° C	mm <sup>2</sup> /s	10,1
Viscosity index			160
Pour point		° C	-39
Flash point Cleveland open cup		° C	226

*The data given in this table are typical values from production and cannot be specifications in any case.*

### PROPERTIES & ADVANTAGES

- **Excellent** anti wear and extreme pressure **performances**
- **Good protection** against rust and corrosion.
- Good anti-foam power
- **Excellent friction coefficient** well adapted to immersed brakes
- **Excellent oxidation** and shear resistance
- **Very good stability** in service

### PERFORMANCES

**AGCO Massey Ferguson** CMS M1145// CMS M1143 (Exceeds M 1135/ M1141)

**CNH Case/New-Holland (Fiat)** : FNHA-2-C-201 (Exceeds FNHA-2-C-200A/C-200)

MAT 3525 (Ford M2C-134-D)

**John Deere** : **JDM J20C** (Exceeds JOHN DEERE J20A)

**Volvo VME** : **WB-101**

**ZF** : TE-ML-03E, TE-ML-05F and TE-ML-06K

**Renault** : when Renault GA 12 standard is recommended (ARES, CELTIS, New Ares, ...)

**API GL4**, **ALLISON C4**, **ISO HV 46/68**

**Also meets service requirement of most of tractors and of many public works machinery equipped with transmissions and immersed brakes :**

**CASE IH** (MS 1206, MS 1207 and MS 1209 Norms); **Deutz** Allis,

**Komatsu Dresser** (B-06-001/-002 norms), **Kubota** UDT, **Steyr**, **White Farm**, ...

