



L'huile des records du monde

MVX 1000 4T – SAE 10W-50

100 % synthetic oil for 4 stroke motorcycle engines

USES

Especially recommended for hyper sport motorcycles equipped with the latest technologies, and used in all service conditions, even the most severe ones including competition, all year-round. Also for the lubrication of integrated gearboxes, provides increased protection of the box/gearing unit (JASO MA2). Keeps engine performances in extreme driving conditions and during long distance trips at high speed.

Exceeds widely the requirements of the main motorbikes manufacturers.

MAIN CHARACTERISTICS

		Units	SAE 10W-50
Density	20° C	kg/m ³	862
Kinematic viscosity	40° C	mm ² /s	137
Kinematic viscosity	100° C	mm ² /s	20
Viscosity Index			168
Pour Point		° C	-39
Flash Point Cleveland open cup		° C	>210
Dynamic viscosity	-25° C	mPa.s	6000


The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- SAE 10W-50 grade for an excellent stability at high temperature and an optimal lubrication at start up.
- Highly shear-resistant viscosity index improvers keep the viscosities in service.
- Excellent detergent/dispersant properties for a cleaner engine.
- Low volatility allows reducing the oil consumption.
- The high coefficient of friction as per JASO MA2 requirements prevents slipping clutches.

HOMOLOGATION

JASO MA2



JASO T903-2011
PERFORMANCE IS GUARANTEED by
YACCO S.A.S.

SPECIFICATION

API SL

