



L'huile des records du monde

# SVX 500 SNOW 2T

## Semi-synthetic oil for 2-stroke snowmobile engines

### APPLICATIONS

High quality semi-synthetic oil specifically developed for use in 2-Stroke snowmobile engines equipped with carburettor or fuel-injection system. Suitable for separated or pre-mix lubrications. Mixing ratio from 2% to 4% according to manufacturers' requirements.

### MAIN CHARACTERISTICS

	Units	Typical values
Density at 20° C		868
Kinematic viscosity at 40° C	mm <sup>2</sup> /s	80
Kinematic viscosity at 100° C	mm <sup>2</sup> /s	11
Viscosity index		125
Pour point	° C	-36
Flash point Cleveland open cup	° C	113
Colour		Blue

*The data given in this table are typical values from production and cannot be considered as specifications.*

### PROPERTIES & ADVANTAGES

- Low pour point that allows to be used in separated lubrication systems at low temperature
- Prevents clogged exhaust pipe
- High internal engine protection against **rust**
- Very good protection of cylinder/piston/piston rings against **seizing**
- **Colored blue** to be easily detected in the fuel
- Prevents **fouling spark plugs** and piston ring gumming

### PERFORMANCES

API TC  
JASO FD  
ISO-L-EGD

