



L'huile des records du monde

# TRANSPRO 25 SAE 15W-40 – TBN 15

## Detergent mineral oil for Diesel and gasoline engines

### APPLICATIONS

Detergent mineral oil developed to meet the technical requirement of EURO V & VI Tier 4 & Tier 3 low emissions Diesel engines using EGR//SCR technology (Adblue), when the use of SAE 15W40 ACEA E7 or API CI-4 lubricants is specified by the manufacturer.

Suitable for most supercharged or atmospheric Diesel engines: trucks, construction & agricultural equipment, stationary engines, generators, marine engines...

It is also suitable for gasoline and Diesel engines in mixed fleet of vehicles when the manufacturer recommends the use of an **API SL/CF** or **ACEA A3/B4 SAE 15W40** lubricant.

### MAIN CHARACTERISTICS

		Units	15W-40
Density at	20° C	kg/m <sup>3</sup>	870
Kinematic viscosity at	40° C	mm <sup>2</sup> /s	102
Kinematic viscosity at	100° C	mm <sup>2</sup> /s	14.7
Viscosity Index			150
Pour Point		° C	-30
Flash Point Cleveland open cup		° C	220
T.B.N		mg KOH/g	15
Dynamic viscosity at	-20° C	mPa.s	5500

*The data given in this table are typical production values and cannot be considered as specifications.*

### PROPERTIES & ADVANTAGES

- Multigrade SAE 15W40 “all season” engine oil
- Highly dispersant and detergent properties (TBN 15 mgKOH/g). Keeps the engine clean, sludge- and deposits-free, especially when running on high-sulfur Diesel.
- Increased protection against bore polishing in Diesel engines
- Excellent shear resistance provides a stable oil viscosity in service

### SPECIFICATIONS

ACEA E7; ACEA A3/B4; API CI-4/SL

Volvo VDS-3; Renault V.I. RLD-2; Mack EO-M Plus

Man M 3275; Mercedes MB 228.3; M.T.U Type 2; Deutz DQC III-10

Caterpillar ECF-1a; Cummins 20076//20077;

Baudouin service B avec carburant contenant jusqu'à 0.7% de soufre

\* For DPF engines, depending on OEM specification, we recommend :

ACEA E9 & API CJ-4: TRANSPRO 65M 5W30; TRANSPRO 6510W40 & TRANSPRO 40S FE 10W30/ 40S LE 10W40/ 40 LE 15W40

ACEA E6: TRANSPRO 65M 5W30; TRANSPRO 65S 10W40 et TRANSPRO 6510W40

