



VX 600 - SAE 5W-30

Synthetic oil for gasoline and Diesel engines

USES

Synthetic oil recommended for gasoline and Diesel engines without particle filter (DPF/GPF).
Universal oil suitable for urban and high rpm motorway use.

Specifications:

ACEA A3/B3

API SL/CF

MAIN PHYSICAL DATA

		Methods	Units	10W-30
Density at	20°C	ASTM D4052	kg/m ³	855
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	70
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	12
Viscosity index		ASTM D2270		169
Dynamic viscosity at	- 30°	ASTM D5293	mPa·s	6600
Sulphated ash		ASTM D874	% mass	1
Total Base Number (TBN)		ASTM D2896	mgKOH/g	8

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Outstanding stability at high temperatures.
- ▶ Very good detergent/dispersant properties.
- ▶ Maintains its rheological and chemical properties all year round.
- ▶ Extends the service life of the engine.
- ▶ Keeps the engine clean even under severe service conditions.
- ▶ Ensures the engine's original settings are maintained.
- ▶ Extremely quick oil flow upon start-up.



 facebook.com/yaccosas

 twitter.com/yaccosas

 youtube.com

