



VX 100 - SAE 15W-40

Superior mineral oil for high performance gasoline and diesel engines

USES

Designed for use in all kinds of daily driving conditions, including roads, motorways, urban traffic, etc.

Provides excellent lubrication and year-round protection for turbocharged and naturally aspirated gasoline and diesel engines.

Compatible with catalytic converters.

Specifications:

ACEA A3/B4

API SL/CF



MAIN PHYSICAL DATA

		Methods	Units	15W-40
Density at	20°C	ASTM D4052	kg/m ³	871
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	102
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	14.5
Viscosity index		ASTM D2270		143
Pour point		ASTM D97	°C	-33
Cleveland Open Cup Flash Point		ASTM D92	°C	220
Dynamic viscosity at	-20°C	ASTM D5293	mPa·s	6200
HTHS viscosity (150 °C)		CEC L-036-90	mPa·s	3.8
Sulphated ash		ASTM D874	% mass	1.36
Total Base Number (TBN)		ASTM D2896	mgKOH/g	11

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ SAE 15W-40 grade viscosity is recommended for year-round lubrication.
- ▶ Outstanding anti-wear properties which exceed ACEA A3/B4 and API SL/CF requirements.
- ▶ Excellent detergent/dispersant properties keep gasoline and diesel engines clean.
- ▶ Outstanding oxidation resistance means excellent lubrication until the next oil change.
- ▶ Reduces friction and extends the service life of the engine.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

