



# HX 100 4T - SAE 15W-40

Premium mineral oil for 4-stroke engines of gardening equipment

## USES

Suitable and recommended for the lubrication of lawnmowers, tillers and mini-tractors used in **normal conditions**.

Compatible with any type of fuel (leaded/unleaded gasoline and diesel).

## Specifications:

API SL/CF (exceeds API SJ/SH/SG/SF)



## MAIN PHYSICAL DATA

		Methods	Units	15W40
Density at	20°C	ASTM D4052	kg/m <sup>3</sup>	872
Kinematic viscosity at	40°C	ASTM D445	mm <sup>2</sup> /s	106
Kinematic viscosity at	100°C	ASTM D445	mm <sup>2</sup> /s	14.6
Viscosity index		ASTM D2270		142
Pour point		ASTM D97	°C	-30
Cleveland Open Cup Flash Point		ASTM D92	°C	221
Dynamic viscosity at	-20°C	ASTM D5293	mPa·s	6400
HTHS viscosity at	150 °C	CEC L-036-90	mPa·s	3.7
Sulphated ash		ASTM D874	% mass	1.4
Total Base Number (TBN)		ASTM D2896	mgKOH/g	11

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Very good detergent/dispersant properties prevent the formation of deposits.
- ▶ Enhanced anti-wear, anti-corrosion and anti-foam properties for better engine protection.
- ▶ SAE 15W-40 grade formula for use all year round.
- ▶ Outstanding mechanical stability maintains oil performance in service.
- ▶ Excellent oxidation resistance allows optimal performances until the next oil change.



 [facebook.com/yaccosas](https://facebook.com/yaccosas)

 [twitter.com/yaccosas](https://twitter.com/yaccosas)

 [youtube.com](https://youtube.com)

