



# HX 500 2T

Semi-synthetic oil for 2 stroke engines on self-propelled agricultural equipment. Low smoke formula.

## USES

**Designed** for the lubrication of 2-stroke gasoline engines on self-propelled agricultural equipment used at high rpm and/or under severe service conditions.

Suitable for separated lubrication and premix systems.

Mixing ratio: 2 to 3%, depending on the manufacturer's recommendations.

## Specifications:

**API TC**  
**JASO FC**

**HX 500 2T** exceeds the performance levels required by the API (US standards) and JASO (Japanese standards)



## MAIN PHYSICAL DATA

		Methods	Units	Values
Density at	20°C	ASTM D4052	kg/m <sup>3</sup>	869
Kinematic viscosity at	40°C	ASTM D445	mm <sup>2</sup> /s	76
Kinematic viscosity at	100°C	ASTM D445	mm <sup>2</sup> /s	10.9
Viscosity index		ASTM D2270		131
Pour point		ASTM D97	°C	-36
Cleveland Open Cup Flash Point		ASTM D92	°C	114
Dynamic viscosity at	-25°C	ASTM D5293	mPa·s	0.12
Colour				Blue

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Semi-synthetic oil for good performance at high temperatures.
- ▶ Good protection of the engine against corrosion and rust.
- ▶ Very good anti-smoke properties.
- ▶ Pre-diluted oil for easier and quicker mixing with fuel.
- ▶ Dyed blue for easy detection.
- ▶ Avoids spark plug fouling and piston ring gumming.



[facebook.com/yaccosas](https://facebook.com/yaccosas)

[twitter.com/yaccosas](https://twitter.com/yaccosas)

[youtube.com](https://youtube.com)

