

YACCO MAS3 SAE 30

Detergent monograde oil for gardening equipment

USES

Specifically recommended for gasoline and diesel engines of lawnmowers, tillers, mini-tractors and other gardening equipment. Also suitable for transmissions and hydraulic systems when the manufacturer recommends the use of a detergent SAE 30 or ISO VG 100 lubricant.



Specifications:

API SL/CF

MAIN PHYSICAL DATA

	Methods	Units	SAE 30
Density at 20°C	ASTM D4052	kg/m³	889
Kinematic viscosity at 40°C	ASTM D445	mm²/s	104
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11.9
Viscosity index	ASTM D2270		103
Pour point	ASTM D97	°C	-30
Cleveland Open Cup Flash Point	ASTM D92	°C	225
Sulphated ash	ASTM D874	% mass	1
Total Base Number (TBN)	ASTM D2896	mgKOH/g	11

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ SAE 30 grade formula for use all year round, especially in summer season, meeting the specific requirement of some manufacturers.
- ▶ Very good detergent/dispersant properties prevent the formation of deposits.
- ▶ Outstanding mechanical stability maintains oil performance in service.
- ► Enhanced anti-wear, anti-corrosion and anti-foam properties for better engine protection.









