



TRF V6

ISO VG 150 chainsaw oil

USES

This oil has been **specifically** designed for use with chainsaws bar and chain. It is also suitable for lubricating **machine tools and transmission chains** when **ISO VG 150** grade oil is required.

Our full range of chainsaw oils also includes:

→ More viscous oils for use under severe service conditions: YACCO TRF V8 ISO VG 220 and YACCO TRF V12 ISO VG 320.

→ YACCO TRF BIO ISO VG 150 biodegradable oil for maximum protection of the environment and environmentally sensitive areas.



MAIN PHYSICAL DATA

		Methods	Units	TRF V6
Density at	20°C	ASTM D4052	kg/m ³	858
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	150
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	22
Viscosity index		ASTM D2270		174
Pour point		ASTM D97	°C	-33
Cleveland Open Cup Flash Point		ASTM D92	°C	208
Appearance				Ropy
Colour				Green

The data given in this table represents typical production values and should not be taken as specifications.



PROPERTIES & ADVANTAGES

- ▶ Polymer-based formula to create a very adhesive oil film which reduces dripping and spattering.
- ▶ Excellent anti-wear protection.
- ▶ Specific additives ensure excellent lubricating properties.
- ▶ Specific viscosity grade provides perfect lubrication.

facebook.com/yaccos

twitter.com/yaccos

youtube.com

