



MVX 100 4T 20W-50

Mineral oil for 4-stroke engines

USES

Mineral oil for motorcycles and tricycles/tuk-tuk 4-stroke engines. Provides excellent engine protection under any service conditions, particularly in hot climates.

Ideally suited to high mileage engines.

Oil drain intervals according to OEM specification (Bajaj, etc...).

Compatible with catalytic converters.

Specification : API SF

MAIN PHYSICAL DATA

		Methods	Units	20W-50
Density at	20°C	ASTM D4052	kg/m ³	828
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	140
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	18
Viscosity index		ASTM D2270		130
Pour point		ASTM D97	°C	-28
Cleveland Open Cup Flash Point		ASTM D92	°C	232
Dynamic viscosity at	-15°C	ASTM D5293	mPa·s	8500
HTHS viscosity (150°C)		CEC L-036-90	mPa·s	4
Sulphated ash		ASTM D874	% mass	0.6
Total Base Number (TBN)		ASTM D2896	mgKOH/g	5.0

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Reinforced anti-wear protection.
- ▶ SAE 20W50 grade ensures maximum protection at high temperatures, and improves oil pressure in old or high mileage engines.
- ▶ Good detergent-dispersant properties prevent the formation of deposits and keep the engine clean.
- ▶ Extends engine's lifespan.
- ▶ Low volatility allows to reduce oil consumption.



 facebook.com/yaccosas

 twitter.com/yaccosas

 youtube.com

